




























































































ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
4MP CVI Camera				
۱	DH-HAC-HDW1۸۰۹TLMP-A-LED     HDCVI Eyeball Camera	۴۵,۳۰۰,۰۰۰		Max. 15 fps@4K. · 120 dB true WDR, 3D NR. · 24/7 color imaging. · 20 m illumination distance. · Super Adapt. · Built-in MIC(-A) . · 2.8 mm fixed lens · CVI/CVBS/AHD/TVI switchable. · IP67, 12 VDC. Metal
۲	DH-HAC-HFW1۸۰۹TP-A-LED     HDCVI Eyeball Camera	۵۰,۳۷۰,۰۰۰		Max. 15 fps@4K. · 120 dB true WDR, 3D NR. · 24/7 color imaging. · 20 m illumination distance. · Super Adapt. · Built-in MIC(-A) . · 3.6 mm fixed lens · CVI/CVBS/AHD/TVI switchable. · IP67, 12 VDC. Metal
5MP CVI Camera				
۳	DH-HAC-TYA۵IP   HDCVI IR Dome Camera	TIA۵IP=۱۶,۶۵۰,۰۰۰ (lens=۲.۸) ۱۸,۸۶۰,۰۰۰		> Max. 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable · 2.8 mm fixed lens · Max. IR length 20 m, Smart IR · IP67, DC12V
۴	DH-HAC-HDW1۵۰۰TLMP   HDCVI IR Eyeball Camera	-		Max 25 fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · 2.8 mm fixed lens · Max. IR length 30 m, Smart IR · IP67, DC12V Metal throughout the whole casing
۵	DH-HAC-HDW1۵۰۰TRQP-A    HDCVI IR Dome Camera	۲۱,۱۵۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · Quick-to-install eyeball saves installation time · Built-in mic (-A) · CVI/CVBS/AHD/TVI switchable · 2.8 mm fixed lens (2.8 mm optional) · Max. IR length 25 m, Smart IR · IP50, DC12V
۶	DH-HAC-HDW1۵۰۰TLQP-A    HDCVI IR Dome Camera	۲۲,۷۰۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · Quick-to-install eyeball saves installation time · 3.6 mm fixed lens (2.8 mm optional) · Built-in mic · Max. IR length 30 m, Smart IR · IP67, DC12V
۷	DH-HAC-HDW1۵۰۰TQP-A    HDCVI Quick-to-install IR Eyeball Camera	۲۳,۴۰۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens (2.8 mm, 6 mm optional) · Built-in mic(-A) · Max. IR length 40 m, Smart IR · IP67, 12V DC
۸	DH-HAC-HDW1۵۰۰TMQP-A    HDCVI Quick-to-install IR Eyeball Camera	۲۶,۵۵۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · Quick-to-install eyeball saves installation time · 3.6 lenz · Built-in mic(-A) · Max. IR length 60 m, Smart IR · IP67, DC12V
۹	DH-HAC-HDW1۵۰۹TLQP-LED   HDCVI IR Dome Camera	۲۹,۷۷۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · 120dB true WDR, 3D NR · 24/7 color imaging · 20 m illumination distance · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens · IP67, 12 V DC
۱۰	DH-HAC-HDW1۵۰۹TLQP-A-LED    HDCVI IR Dome Camera	۳۱,۹۹۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · 120dB true WDR, 3D NR · 24/7 color imaging · 20 m illumination distance · CVI/CVBS/AHD/TVI switchable · Built-in mic (-A) · 2.8 mm fixed lens (2.8 mm optional) · IP67, 12 V DC
۱۱	DH-HAC-HDW1۵۰۹TP-A-LED    HDCVI IR Dome Camera	۱۵۰۹TP-LED=۳۲,۹۰۰,۰۰۰ (lens=۲.۸) ۳۳,۸۵۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · 120 dB true WDR, 3D NR · 24/7 color imaging · 40 m illumination distance · CVI/CVBS/AHD/TVI switchable · Built-in mic (-A) · 3.6 mm fixed lens (2.8 mm optional) · IP67, 12 V DC Full Metall
۱۲	DH-HAC-HFW1۵۰۰TP   HDCVI IR Bullet Camera	۲۴,۹۰۰,۰۰۰		Max 25fps@5MP (16:9 video output) CVI/CVBS/AHD/TVI switchable 2.8 mm fixed lens Max. IR length 30 m, Smart IR IP67, DC12V
۱۳	DH-HAC-HFW1۵۰۰TP-A    HDCVI IR Bullet Camera	۲۶,۸۳۰,۰۰۰		Max. 20fps@5MP Built-in mic HD and SD output switchable 3.6 mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V
۱۴	DH-HAC-HFW1۵۰۰CMP   HDCVI IR Bullet Camera	۲۱,۸۸۰,۰۰۰		Max 25 fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens · Max. IR length 30m, Smart IR · IP67, 12V DC *Full metal case

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
۱۵	DH-HAC-BYA۵IP HDCVI IR Bullet Camera 5 MP megapixel	BI۵IP=۱۶,۶۵۰,۰۰۰ (lens=۲.۸) ۱۸,۸۳۰,۰۰۰		5MP HDCVI Fixed IR Bullet Camera * Max. 25 fps@5MP (16:9 video output) * CVI/CVBS/AHD/TVI switchable * 3.6mm fixed lens * Max. IR length 20 m, Smart IR * IP67, DC12V * Casing Aluminium
۱۶	DH-HAC-HFW۱۵۰۰TLP HDCVI IR Bullet Camera 5 MP megapixel STARLIGHT	۲۰,۰۰۰,۰۰۰		* Max 25 fps@5MP (16:9 video output) * CVI/CVBS/AHD/TVI switchable * 3.6 mm fixed lens * Max. IR length 40 m, Smart IR * IP67, DC12V
۱۷	DH-HAC-HFW۱۵۰۰DP-SY HDCVI IR Bullet Camera 5 MP megapixel STARLIGHT	۲۹,۲۰۰,۰۰۰		* Max 25 fps@5MP (16:9 video output) * CVI/CVBS/AHD/TVI switchable * 3.6 mm fixed lens (6 mm, 8 mm optional) * Max. IR length 80 m, Smart IR * IP67, 12V DC * Metal
۱۸	DH-HAC-HFW۱۵۰۰RP-Z-IRE۶ HDCVI Motorized IR Bullet Camera 5 MP megapixel	۴۸,۶۸۰,۰۰۰		Max. 20fps@5MP * HD and SD output switchable * 2.7-12mm motorized lens * Max. IR length 60m, Smart IR * IP67, DC12V * Metal throughout the whole casing
۱۹	DH-HAC-HFW۱۵۰۹TLMP-A-LED HDCVI IR Bullet Camera 5 MP megapixel Full-colour	۳۳,۷۰۰,۰۰۰		Max 25 fps@5MP (16:9 video output) * 120 dB true WDR, 3D NR * 24/7 color imaging * 40 m illumination distance * CVI/CVBS/AHD/TVI switchable * 3.6 mm fixed lens (2.8 mm optional) * IP67, 12 V DC
۲۰	DH-HAC-HFW۱۵۰۹TMP-A-LED HDCVI IR Bullet Camera 5 MP megapixel Full-colour	۳۹,۶۷۰,۰۰۰		* The parameters and datasheets below can only be applied to 1509-S2 series. * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. * Max 25 fps@5MP (16:9 video output) * 120 dB true WDR, 3DNR * 40 m illumination distance * Built-in mic * 3.6 mm fixed lens * IP67, 12V DC , Metal
۲۱	DH-HAC-HFW۱۵۰۹CP-LED HDCVI IR Bullet Camera 5 MP megapixel Full-colour	۲۸,۴۵۰,۰۰۰		* Max 25 fps@5MP (16:9 video output) * 120 dB true WDR, 3D NR * 24/7 color imaging * 20 m illumination distance * CVI/CVBS/AHD/TVI switchable * Built-in mic (-A) * 3.6 mm fixed lens (2.8 mm optional) * IP67, 12 V DC
۲۲	DH-HAC-HFW۱۵۰۹TP-A-LED HDCVI IR Bullet Camera 5 MP megapixel Full-colour	۱۵۰۹TP-LED=۳۲,۱۹۰,۰۰۰ (lens=۲.۸) ۳۵,۱۵۰,۰۰۰		* Max 25 fps@5MP (16:9 video output) * 120 dB true WDR, 3D NR * 24/7 color imaging * 20 m illumination distance * CVI/CVBS/AHD/TVI switchable * Built-in mic * 3.6 mm fixed lens (2.8 mm optional) * IP67, PoC (only CVI)/12 V±30% DC
۴MP CVI Camera				
۲۳	DH-HAC-HFW۱۴۰۰TP HDCVI IR Bullet Camera 4 MP megapixel	۲۳,۷۵۰,۰۰۰		Max 30fps@4MP * HD and SD output switchable * 2.8 mm fixed lens * Max. IR length 30m, Smart IR * IP67, DC12V * Metal
۲MP CVI Camera				
۲۴	DH-HAC-HUM۳۲۰۱B-P 2MP Starlight HDCVI Pinhole Camera 2 MP megapixel STARLIGHT	۳۱,۸۵۰,۰۰۰		* Starlight, 120dB true WDR, 3DNR * Max 30fp@1080P * HD and SD output switchable * 2.8mm fixed lens * Audio in interface * DC12V
۲۵	DH-HAC-TIA۲IP HDCVI IR Dome Camera 2 MP megapixel	۹,۷۴۰,۰۰۰		2MP HDCVI IR Eyeball Camera * Max. 30fps@1080P * Casing Plastic * HD and SD output switchable * 3.6mm fixed lens * Max. IR length 20m, Smart IR * DC12V
۲۶	DH-HAC-TYA۲IP HDCVI IR Dome Camera 2 MP megapixel	Lenz ۲.۸=۱۲,۲۳۰,۰۰۰ ۱۱,۸۵۰,۰۰۰		2MP HDCVI IR Eyeball Camera * Max. 30fps@1080P * HD and SD output switchable * 3.6mm fixed lens * Max. IR length 20m, Smart IR * Casing Aluminium * IP67, DC12V

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
٢٧	DH-HAC-BIA٢١P  HDCVI IR Bullet Camera	lenz ٣.٦=٩,٧٤٠,٠٠٠ ١٠,٠٠٠,٠٠٠		<ul style="list-style-type: none"> Max. 30fps@ 1080P HD and SD output switchable 2.8mm fixed lens Max. IR length 20m, Smart IR IP67, DC12V Casing plastic
٢٨	DH-HAC-B٢A٢١P  HDCVI IR Bullet Camera	١١,٨٥٠,٠٠٠		<ul style="list-style-type: none"> 2MP HDCVI IR Bullet Camera Max. 30fps@1080P HD and SD output switchable 3.6mm fixed lens Max. IR length 20m, Smart IR Casing Aluminium IP67, DC12V
٢٩	DH-HAC-HDW١٢٠٠TRQP-A   HDCVI IR Dome Camera	١٣,٩٥٠,٠٠٠		<ul style="list-style-type: none"> 2MP HDCVI Quick-to-install IR Eyeball Camera Max 30fps@1080P Built-in mic (-A) Casing Plastic 3.6mm fixed lens Max. IR length 25m, Smart IR IP50, DC12V
٣٠	DH-HAC-HDW١٢٠٠MP  HDCVI IR Dome Camera	١٥,٣٣٠,٠٠٠		<ul style="list-style-type: none"> 2MP HDCVI IR Eyeball Camera Max 30fps@1080P HD and SD output switchable Casing Metal throughout the whole casing 2.8mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V
٣١	DH-HAC-HDW١٢٠٠TQP-A   HDCVI IR Dome Camera	١٧,٢٠٠,٠٠٠		<ul style="list-style-type: none"> Max 30fps@1080P Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable 3.6mm fixed lens (2.8mm, 6mm optional) Built-in mic(-A) Max. IR length 40m, Smart IR IP67, DC12V
٣٢	DH-HAC-HDW١٢٠٠EMP-A   HDCVI IR Dome Camera	١٧,٧٨٠,٠٠٠		<ul style="list-style-type: none"> Max 30fps@1080P HD and SD output switchable 2.8mm fixed lens (2.8mm, 6mm optional) Built-in mic(-A) Max. IR length 50m, Smart IR IP67, DC12V
٣٣	DH-HAC-HDW١٢٠٩TLQP-LED  ٢MP HDCVI IR Dome Camera Full-colour	-		<ul style="list-style-type: none"> 24/7 color imaging 20 m illumination distance Max. 30 fps@ 1080p Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable Fixed lens 2.8mm IP67 12V±30% DC
٣٤	DH-HAC-HDW١٢٠٩TLQP-A-LED   HDCVI IR Dome Camera Full-colour	١٨,٠٠٠,٠٠٠		<ul style="list-style-type: none"> 2MP Full-color HDCVI Quick-to-install Eyeball Camera Max. 30fps@1080P 24/7 color imaging 20 m illumination distance Built-in mic(-A) * Fixed lens(2.8mm) Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable Casing: Inner core: metal + plastic/ Cover: plastic Pedestal: plastic * IP67, DC12V
٣٥	DH-HAC-HDW١٢٠٩TQP-A-LED   HDCVI IR Bullet Camera Full-colour	١٢٠٩TQP-LED=١٦,٤٢٠,٠٠٠ ١٩,١٤٠,٠٠٠		<ul style="list-style-type: none"> 24/7 color imaging 40 m illumination distance Max. 30 fps@ 1080p Built-in mic (-A) Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable Fixed lens 2.8 mm IP67, 12V±30% DC
٣٦	DH-HAC-HFW١٢٠٠CMP  ٢MP HDCVI IR Bullet Camera	١٤,٧٧٠,٠٠٠		<ul style="list-style-type: none"> Max 30fps@1080P CVI/CVBS/AHD/TVI switchable 3.6mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V full metal case
٣٧	DH-HAC-HFW١٢٠٠TP  HDCVI IR Bullet Camera	١٥,٥٩٠,٠٠٠		<ul style="list-style-type: none"> Max 30fps@ 1080P HD and SD output switchable 2.8 3.6 mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V
٣٨	DH-HAC-HFW١٢٠٠TP-A   HDCVI IR Bullet Camera	١٧,٨٤٠,٠٠٠		<ul style="list-style-type: none"> Max 30fps@ 1080P HD and SD output switchable Built-in mic 3.6mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
۳۹	DH-HAC-HFW1۰۰DP HDCVI IR Bullet Camera 2 MP megapixel	۱۸,۶۷۰,۰۰۰		2MP HDCVI IR Bullet Camera • Max 30fps@1080P • CVI/CVBS/AHD/TVI switchable • 3.6mm fixed lens • Max. IR length 80m, Smart IR • IP67, DC12V • Casing Metal throughout the whole casing
۴۰	DH-HAC-HFW1۰۰THP-1A YMP HDCVI IR Bullet Camera 2 MP megapixel	۱۸,۶۷۰,۰۰۰		Max 30fps@1080p • HD and SD output switchable • 3.6 mm fixed lens (2.8 mm, 6 mm optional) • Max. IR length 80 m, Smart IR • IP67, DC 12V • Metal front cover+plastic main body+metal bracket
۴۱	DH-HAC-HFW1۰۹TLMP-LED YMP HDCVI IR Bullet Camera Full-colour 2 MP megapixel	۱۲۰۹TLMP-A-LED=۲۰,۷۷۰,۰۰۰ ۱۹,۷۰۰,۰۰۰		24/7 color imaging • 40 m illumination distance • Max. 30 fps@1080p • Built-in mic (-A) • CVI/CVBS/AHD/TVI switchable • Fixed lens 3.6 mm • IP67, 12V±30% DC
۴۲	DH-HAC-HFW1۰۰SP YMP HDCVI IR Bullet Camera 2 MP megapixel	۱۵,۱۷۰,۰۰۰		Max 30fps@1080P • HD and SD output switchable • 3.6mm fixed lens (2.8 mm, 6 mm optional) • Max. IR length 30m, Smart IR • IP67, DC12V • METAL
۴۳	DH-HAC-HFW1۰۹CMP-A-LED HDCVI IR Bullet Camera 2 MP megapixel Full-colour	۲۰,۰۹۰,۰۰۰		• Full-color starlight • 20 m illumination distance • Max. 30fps@1080P • CVI/CVBS/AHD/TVI switchable • Fixed lens 3.6 mm • IP67, 12V±30% DC • Metal
۴۴	DH-HAC-HFW1۲۳۹TP-A-LED 2 MP megapixel Full-colour	۲۳,۱۷۰,۰۰۰		Full-color starlight • 20m LED distance • Max. 30fps@1080P • CVI/CVBS/AHD/TVI Switchable • Built-in mic(-A) • 3.6mm fixed lens (2.8mm Optional) • IP67, DC12V±30% DC
۴۵	DH-HAC-HFW1۰۹CP-A-LED HDCVI IR Bullet Camera 2 MP megapixel Full-colour	۱۶,۹۰۰,۰۰۰		• Full-color starlight • 20 m illumination distance • Max. 30fps@1080P • CVI/CVBS/AHD/TVI switchable • Fixed lens 2.8 mm • IP67, 12V±30% DC • Plastic
PTZ Camera				
۴۶	DH-SD۴۹۲۲۵-HC-LA ۲۵x Starlight IR PTZ HDCVI Camera 2 MP megapixel	۲۳۳,۲۰۰,۰۰۰		• 1/2.8" 2Megapixel STARVIS™ CMOS • Powerful 25x optical zoom • Starlight technology • 120 dB true WDR, 3D DNR • Max. 25/30 fps@1080P, 25/30/50/60 fps@720P • IR distance up to 100 m • IP66

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
XVR Fchannel				
۴۷	DH-XVRIB۰۴-I Penta-brid/۱۰۸۰N/۷۲۰PCooper 4 CH Wiz Sense	۲۶,۰۰۰,۰۰۰		4 Channel Penta-brid 1080N/1HDD WizSense * H.265+/H.265 dual-stream video compression > Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth * 8-channel: the 1st channel 1080N/720p(1 fps-25/30 fps), others 1080N/720p(1 fps-15 fps); 960H/D1/CIF/(1 fps-25/30 fps) 1 SATA port, up to 6 TB capacity 1 HDMI; 1 VGA * Supports HDCVI/AHD/TVI/CVBS/IP video inputs
۴۸	DH-XVRIB۰۴-I (۷۲.۰) Penta-brid/۱۰۸۰N/۷۲۰PCooper 4 CH Wiz Sense	۲۶,۰۰۰,۰۰۰ SSD SUPPORT		4 Channel Penta-brid 1080N/1HDD WizSense * H.265+/H.265 dual-stream video compression > Max 5 channels IP camera inputs, each channel up to 2MP; Max 20 Mbps incoming bandwidth * 8-channel: the 1st channel 1080N/720p(1 fps-25/30 fps), others 1080N/720p(1 fps-15 fps); 960H/D1/CIF/(1 fps-25/30 fps) 1 SATA port, up to 6 TB capacity 1 HDMI; 1 VGA * Supports HDCVI/AHD/TVI/CVBS/IP video inputs
۴۹	DH-XVR۵۱۰۴HS-I۳ Penta-brid/۵M-N/۱۰۸۰P 4 CH Wiz Sense Supports HDCVI/AHD/TVI/CVBS/IP video inputs	۴۸,۱۵۰,۰۰۰		4 Channel Penta-brid 5M-N/1080p 1U 1HDD WizSense * H.265+/H.265 dual-stream video compression 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF Main stream: All channel 5M-N (1 fps-10 fps); 4M-N/1080p (1 fps-15 fps); 1080N/720p/960H/D1/CIF (1 fps-25/30 fps) Sub stream: D1/CIF (1 fps-15fps) * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 6 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth * IoT & POS functionalities
۵۰	DH-XVR۵۱۰۴HS-۴KL-I۳ Penta-brid/۴K-N/۵MP Compact 4 CH Wiz Sense Supports HDCVI/AHD/TVI/CVBS/IP video inputs	۶۳,۵۴۰,۰۰۰		4 Channel Penta-brid 5MP Compact 1U 1HDD WizSense * H.265+/H.265 dual-stream video compression * Resolution 4K; 6MP; 5MP; 4MP; 3MP; 4M-N; 1080P; 720P; 960H; D1; CIF /Sub stream: 960H (1 fps-15 fps); D1/CIF (1 fps-25/30 fps) * Supports Full-channel AI-Coding/ * Supports HDCVI/AHD/TVI/CVBS/IP video inputs Main stream: All channel 4K (1 fps-7 fps); 6MP (1 fps-10 fps); 5MP (1 fps-12 fps); 4MP/3MP (1 fps-15 fps); 4M-N/1080p/720p/960H/D1/CIF (1 fps-25/30 fps); * Max 8 channels IP camera inputs, each channel up to 8MP; Max 64 Mbps incoming bandwidth* * IoT & POS functionalities
XVR Achannel				
۵۱	DH-XVRIB۰۸-I Penta-brid/۱۰۸۰N/۷۲۰PCooper 8 CH Wiz Sense	۳۲,۱۵۰,۰۰۰		8 Channel Penta-brid 1080N/1U 1HDD WizSense * H.265+/H.265 dual-stream video compression * 8-channel: the 1st channel 1080N/720p(1 fps-25/30 fps), others 1080N/720p(1 fps-15 fps); 960H/D1/CIF/(1 fps-25/30 fps) * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth
۵۲	DH-XVRIB۰۸-I (۷۲.۰) Penta-brid/۱۰۸۰N/۷۲۰PCooper 8 CH Wiz Sense	۳۲,۱۵۰,۰۰۰ SSD SUPPORT		8 Channel Penta-brid 1080N/1U 1HDD WizSense * H.265+/H.265 dual-stream video compression * 8-channel: the 1st channel 1080N/720p(1 fps-25/30 fps), others 1080N/720p(1 fps-15 fps); 960H/D1/CIF/(1 fps-25/30 fps) * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 10 channels IP camera inputs, each channel up to 6MP; Max 40 Mbps incoming bandwidth
۵۳	DH-XVR۵۱۰۸HS-I۳ Penta-brid/۵M-N/۱۰۸۰P 8 CH Wiz Sense Supports HDCVI/AHD/TVI/CVBS/IP video inputs	۶۸,۳۰۰,۰۰۰		8 Channel Penta-brid 5M-N/1080p 1U 1HDD WizSense * H.265+/H.265 dual-stream video compression 5M-N; 4M-N; 1080p; 1080N; 720p; 960H; D1; CIF Main stream: All channel 5M-N (1 fps-10 fps); 4M-N/1080p (1 fps-15 fps); 1080N/720p/960H/D1/CIF (1 fps-25/30 fps) Sub stream: D1/CIF (1 fps-15fps) * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 12 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps incoming bandwidth * IoT & POS functionalities
۵۴	DH-XVR۵۱۰۸HS-۴KL-I۳ Supports HDCVI/AHD/TVI/CVBS/IP video inputs 8 CH Wiz Sense	۱۱۸,۰۰۰,۰۰۰		H.265+/H.265 dual-stream video compression * Supports Full-channel AI Coding * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 16 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth * Up to 8 channels video stream (analog channel) Perimeter Protection * Up to 8 channels video stream (analog channel) SMD Plus * Up to 2 channels video stream (analog channel) human face recognition * IoT & POS functionalities

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
XVR ۱۶channel				
۵۵	<p>DH-XVR1۶I-I</p> <p>Penta-brid/1۰۸۰N/۷۲۰P Cooper</p> <p>16 CH</p> <p>Wiz Sense</p>	۶۳,۳۰۰,۰۰۰	 <p>16 Channel Penta-brid 1080N/ 1U 1HDD WizSense * H.265+/H.265 dual-stream video compression the 1st channel 1080N/720p (1 fps-25/30 fps), others 1080N/720p (1 fps-15 fps); 960H/D1/HD1/BCIF/CIF/QCIF (1 fps-25/30 fps) * Supports HDCVI/AHD/TVI/CVBS/IP video inputs * Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth</p>	
۵۶	<p>DH-XVR۵۲۱۶AN-۴KL-۱۲</p> <p>16 CH</p> <p>Wiz Sense</p>	۱۹۳,۶۲۰,۰۰۰	 <p>Embedded processor · H.264+/H.264 dual-stream video compression · Support HDCVI/AHD/TVI/CVBS/IP video inputs · Max 12/24 channels IP camera inputs, each channel up to 8MP · Max 48/96Mbps Incoming Bandwidth · Smart Search and Intelligent Video System</p>	
۵۷	<p>DH-XVR۵۲۱۶AN-۱۳</p> <p>16 CH</p> <p>Wiz Sense</p>	-	 <p>· H.265+/H.265 dual-stream video compression · Supports Full-channel AI Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth · Up to 4 channels video stream (analog channel) Perimeter Protection · IoT & POS functionalities</p>	
۵۸	<p>DH-XVR۵۱۱۶HS-۱۳</p> <p>16 CH</p> <p>Wiz Sense</p>	۱۲۰,۰۰۰,۰۰۰	 <p>16 Channel Penta-brid 5M-N/1080P Compact 1U 1HDD WizSense Digital Video Recorder H.265+/H.265 dual-stream video compression Supports Full-channel AI Coding Supports HDCVI/AHD/TVI/CVBS/IP video inputs Max 24 channels IP camera inputs, each channel up to 6MP; Max 128Mbps incoming bandwidth IoT & POS functionalities</p>	
۵۹	<p>DH-XVR۵۱۱۶H-۴KL-۱۳</p> <p>Penta-brid/۴K-N/۵MP</p> <p>16 CH</p> <p>Wiz Sense</p> <p>Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p>	۱۵۸,۱۷۰,۰۰۰	 <p>H.265+/H.265 dual-stream video compression. · Supports Full-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth. · Up to 8 channels video stream (analog channel) Perimeter Protection. · Up to 16 channels video stream (analog channel) SMD Plus. · Up to 2 channels video stream (analog channel) human face recognition. incoming bandwidth: 128 Mbps</p>	
۶۰	<p>DH-XVR۵۲۱۶AN-۴KL-۱۳</p> <p>Penta-brid/۴K-N/۵MP</p> <p>16 CH</p> <p>Wiz Sense</p> <p>Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p>	۲۱۷,۲۰۰,۰۰۰	 <p>H.265+/H.265 dual-stream video compression. · Supports Full-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 8MP; Max 128 Mbps incoming bandwidth. · Up to 2 channels video stream (analog channel) Perimeter Protection · Up to 16 channels video stream (analog channel) SMD Plus. · Up to 2 channels video stream (analog channel) human face recognition. · IoT & POS functionalities</p>	
XVR ۳۲channel				
۶۱	<p>DH-XVR۵۲۳۲AN-۱۳</p> <p>Penta-brid ۵M-N/1۰۸۰P</p> <p>32 CH</p> <p>Wiz Sense</p> <p>Supports HDCVI/AHD/TVI/CVBS/IP video inputs</p>	۲۳۴,۰۰۰,۰۰۰	 <p>H.265+/H.265 dual-stream video compression. · Supports 16-channel AI-Coding. · Supports HDCVI/AHD/TVI/CVBS/IP video inputs. · Max 32 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth. · Up to 2 channels video stream (analog channel) Perimeter Protection. · Up to 16 channels video stream (analog channel) SMD Plus. · Up to 2 channels video stream (analog channel) human face recognition · IoT & POS functionalities.</p>	