

Model	BL042BP	
Product	PoE Switch--6 ports Switch with 4 100M PoE ports & 2 100M uplink ports	
Ports		
Network Ports:	6	
PoE Port:	4, <b>100Mbps</b> ; RJ45 ports; Max. 30W Output of Single PoE Port Transmission distance:0~100m	
Uplink Port:	2, 100Mbps; Transmission Distance: Default: 0-100m	
Power Indicator	Light on: Powering	
	Light off: No Power	
Port 1-6 indicator	Light off: Link is disconnected	
	Red light on: Powering but data disconnected	
	Light flash quickly: Data Transmitting	
Standard		
Network Protocol:	IEEE802.3i/802.3u/802.3x/802.3af	
Performance		
Switching Capacity:	1.2 Gbps Full duplex	
Packet Forwarding Rate:	0.1488Mpps/port	
Forwarding Mode:	Store-and-forward	
MAC Address Table:	2K	
Vlan/Extend	No Support	
Power Over Ethernet		
PoE Standard:	IEEE802.3af, IEEE802.3at	
PoE Power Supply	1/2(+),3/6(-)	
Transmission Distance:	0-100m/100Mbps	
PoE Feature	All ports support MDI/MDIX	
General		
Power Source:	Bult-in Power Supply	
	Input: 110-264V AC, 50/60Hz	
PoE Power Budget:	65W 52V	
Power Consumption:	<5W	
ESD	Air discharge: 1.5KV	
	Contact discharge: 1.5KV	
Anti-Thunder Level	Common mode: 1.5KV	
	Differential mode: 1.5KV	
Working Temperature:	-10℃-50℃	
Humidity:	10%-95% , non-condensing	
Storage Temperature:	-40℃-70℃	

Color	Black
Weight:	0.5kg ( include input cable & packaging )
Dimension(L×W×H):	170*90*40 mm

Product Picture

