

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
WIFI				
۱	DH-H2A Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 	۳۲,۴۵۰,۰۰۰		<p>2-MP 1/3.2" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 2 MP (1920 × 1080)@25 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. IR illumination distance is 10 m. - Supports max. 256 G Micro SD card; built-in Mic; built-in speaker. - 5 VDC power supply. - Supports Wi-Fi. - Supports motion detection, human detection.
	DH-H5A Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera 	۳۷,۱۸۰,۰۰۰		<p>5-MP 1/3.2" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 2 MP (1920 × 1080)@25 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. IR illumination distance is 10 m. - Supports max. 256 G Micro SD card; built-in Mic; built-in speaker. - 5 VDC power supply. - Supports Wi-Fi. - Supports motion detection, human detection.
	DH-C5A 5MP Indoor Fixed-focal Wi-Fi Cube Network Camera 	۳۷,۱۸۰,۰۰۰		<p>Pet Detection Two-way Talk Wi-Fi 6 SD Card Built-in Microphone Built-in Speaker Wi-fi Connection Image Rotation 180°</p>
	DH-H1C 1080P H.265 Wi-Fi P&T Camera 	۳۷,۶۰۰,۰۰۰		<p>1080P Full HD Video Motion Detection /Human Detection Smart Color Night Vision Active Deterrence Two-way Talk Built-in Microphone Built-in Speaker Wi-fi Connection Image Rotation 180°</p>
AMP IP Camera				
۲	DOME DH-IPC-HDW1A1TP-S-IL IR Fixed focal Eyeball Network Camera 	۱۹,۷۷۰,۰۰۰		<p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and IR LED, the max. illumination distance is 30 m - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - SMD Plus.
	DH-IPC-HFW1A1TP-AS AMP IR Fixed-focal Bullet WizSense Network Camera 	۱۲۳,۵۵۰,۰۰۰		<p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 80 m. - Alarm: 1 in, 1 out ; audio: 1 in, 1 out ; Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67, IK10 (optional) protection. - SMD Plus.
۳	BULLET DH-IPC-HFW1A1SP-SF Entry IR Fixed-focal Bullet Network Camera 	۹۲,۰۰۰,۰۰۰		<p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 8 MP (3840 × 2160) @15 fps and supports 2688 × 1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, and ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 30 m. - Built-in MIC. - 12 V DC/PoE power supply. - IP67 protection.
	DH-IPC-HFW1A1ISP-S IPC IR Bullet Camera 	۱۲۷,۶۹۰,۰۰۰		<p>Outputs max. 8 MP (3840 × 2160) @15 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps</p> <ul style="list-style-type: none"> - H.265 codec, high compression rate, ultra-low bit rate - max IR distance: 30 m - Rotation mode: WDR, 3D DNR, HLC, BLC, digital watermarking, - Supports max. 256 GB Micro SD card - 12V DC/PoE power support Lens=3.6 mm - IP67 protection / Network RJ-45 (10/100 Base-T) - Min. illumination 0.009 Lux@F2.0
	DH-IPC-HFW1A1SP-S-IL 	۱۲۹,۲۳۰,۰۰۰		<p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - SMD Plus.
	DH-IPC-HFW1A1TP-ZAS IR Vari-focal Bullet WizSense Network Camera 	۱۷۰,۳۸۰,۰۰۰		<p>8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.</p> <ul style="list-style-type: none"> - Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 60 m. - Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.> - Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67, IK10 (optional) protection.

رده	موديل	قيمت	تصوير كالا	مشخصات فني
٥MP IP Camera				
١٢	DH-IPC-HDW٢٥١TP-S IR Fixed-focal Eyeball WizSense Network Camera 	٨٧,٦٩٠,٠٠٠		<p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. - Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply. Inner core: Metal Cover: Plastic - IP67 protection. SMD Plus</p>
١٣	DH-IPC-HFW٢٥١ISP-S Lite AI IR Fixed focal Eyeball Netwok Camera 	٨٧,٦٩٠,٠٠٠		<p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.-Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. Support Triple Stream-H.265 codec, high compression rate, ultra-low bit rate. Built-in IR LED, and the max. illumination distance is 30 m.Supports max. 256 G Micro SD card; - built in MIC. LENS: 2.8 mm - 12 VDC/PoE power supply - IP67 protection.-SMD Plus.</p>
دید در شب رنگي ميكروفون دار				
١٤	DH-IPC-HFW٣٥١EP-AS-LED Full-color Fixed-focal Warm LED Bullet WizSense Network Camera 	١١٨,٤٦٠,٠٠٠		<p>5-MP 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 5 MP (2952 × 1944) @20 fps, and supports 4MP (2688 × 1520) @25/30 fps - H.265 codec, high compression rate, low bit rate - Built-in warm light, max. illumination distance: 30 m - changing audio detection, no SD card, SD card full, SD card error, - Alarm: 1 in, 1 out; Audio: 1 in, 1 out; supports max. 256 G Micro SD card, built in MIC - 12V DC/PoE power supply, easy for installation - IP67 protection - SMD Plus</p>
موتورايز				
١٥	DH-IPC-HFW٢٥١TP-ZS Lite AI IR Vari-focal Bullet Network Camera 	١٢٦,١٥٠,٠٠٠		<p>5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. - Outputs max. 5 MP (2960 × 1668) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 60 m. - Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67, IK10 (optional) protection. - SMD Plus.</p>
١٦	DH-IPC-HFW٣٥١TP-ZS Lite AI IR Vari-focal Bullet Network Camera 	-		<p>5-MP 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 5MP (2592 × 1944)@20 fps - H.265 codec, high compression rate, low bit rate - Built-in IR LED, max. IR distance: 60 m - ROI, SMART IR, H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments - Supports max. 256 G Micro SD card - 12V DC/POE power support - IP67 protection - SMD Metal</p>
٤MP IP Camera				
١٧	DH-IPC-HDW١٤٣١T1P-S IPC IR Dome Camera 	-		<p>*H.265& H.264 dual-stream encoding *20fps@4M(2688×1520) &25/30fps@3M(2304×1296) *WDR(120dB * Length 30m * IP67, *Casing: Metal+Plastic *Ingress Protection IP67 *Focal Length 2.8 mm</p>
١٨	DH-IPC-HDW١٤٣١ISP-S WDR IR Eyeball Network Camera 	٥٢,٥٨٠,٠٠٠		<p>1/3" 4Megapixel progressive CMOS - H.265& H.264 dual-stream encoding - 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) - WDR(120dB), Day/Night(ICR), 3DNR, HLC, AGC, BLC - 2.8 mm fixed lens (3.6mm optional) - Max IR LEDs Length 30m - IP67, PoE Metal+Plastic</p>
ميكروفون دار				
١٩	DH-IPC-HDW١٤٣٠TP-A IPC IR Dome Camera 	٥٤,٦٢٠,٠٠٠		<p>4-MP 1/3" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2560 × 1440)@25/30 fps - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 30 m. - Built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection.</p>
٢٠	DH-IPC-HDW١٤٣١T1P-A IPC IR Dome Camera 	٥٦,١٥٠,٠٠٠		<p>4-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. - Outputs 4 MP (2560 × 1440) @25/30 fps, and supports max. 4 MP (2688 × 1520) @20 fps - Built-in MIC. - 12 VDC/PoE power supply. - IP67 protection.</p>

رديف	موديل	قيمة	تصوير كالا	مشخصات فني
٢١	DH-IPC-HDBW2441EP-S IPC IR Dome Camera 	٦٩,٥٤٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2688 x 1520) @20 fps, and supports 2560 x1440 @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67, IK10 protection. - SMD Plus.
استارلايت و ميكروفون دار				
٢٢	DH-IPC-HDW3441TMP-AS Lite AI IR Fixed focal Eyeball Network Camera 	٧٣,٣٨٥,٠٠٠		<ul style="list-style-type: none"> - 4MP, 1/3" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 x 1520) @30 fps - H.265 codec, high compression rate, low bit rate - Built-in IR LED, max. IR distance: 50 m - Supports max. 256 G Micro SD card, built-in Mic - 12V DC/POE power support - IP67 protection - Lens: 2.8 mm - 4Mp IP67H.
متوهيز				
٢٣	DH-IPC-HDBW3441RP-ZAS-SY Vari-focal Dome WizSense Network Camera 	١٠٩,٢٣٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor - Outputs max. 4 MP (2688 x 1520) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, max. IR distance: 40 m. - ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable Lens=2.7-13.5 mm - Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in,1 out (Only - ZAS supports); max. 256 G Micro SD card; built-in Mic. - 12 VDC/PoE power supply facilitates installation. - IP67, IK10 protection. - SMD 4.0, AI SSA, Metal
دوال لایت				
٢٤	DH-IPC-HDW1439T1P-A-IL 	٦٢,٦٢٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and highdefinition image. - Outputs max. 4 MP (2560 x1440) @25/30 fps. - H.265 codec, high compression rate ultra-low bit rate. - Built-in multi-core light, the max. IR distance is 30 m and the max.warm light distance is 30 m. - Abnormality detection: Motion detection, video tampering, audiodetection, network disconnection, IP conflict, illegal access. - Built in Mic. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - Supports human detection.
دید در شب رنگی				
٢٥	DH-IPC-HDW1439T1-LED 4MP Entry Full-color Fixed-focal Eyeball Network Camera 	٦٠,٠٠٠,٠٠٠		<ul style="list-style-type: none"> - 1/3" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2560 x 1440) @25/30 fps. - Built-in warm light, and the max. illumination distance is 15 m. - ROI, SMART H.264+/H.265+, flexible coding, applicable to various - 12 VDC/PoE power supply. - IP67 protection
دید در شب رنگی ميكروفون دار				
٢٦	DH-IPC-HDW1439T1-A-LED 4MP Entry Full-color Fixed-focal Eyeball Network Camera 	٦٢,٦٢٠,٠٠٠		<ul style="list-style-type: none"> - 1/3" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2560 x 1440) @25/30 fps. - Built-in warm light, and the max. illumination distance is 15 m. - ROI, SMART H.264+/H.265+, flexible coding, applicable to various - 12 VDC/PoE power supply. - IP67 protection
٢٧	DH-IPC-HDW2439TP-AS-LED-SY IPC IR Dome Camera 	٧٦,٩٢٠,٠٠٠		<ul style="list-style-type: none"> * 4MP / * H.265 codec * 12V DC/ * Outputs 4MP (2560 x 1440) @ 25/30 fps, * Max. supports 4MP (2688 x 1520) @ 20 fps * Built-in warm lights max WDR 120 dB * illumination distance: 30 m Focal Length 3.6 mm & 2.8mm * Casing Inner core: metal; cover: plastic (pedestal: plastic) * Supports max. 256 GB Micro SD card and built-in Mic
٢٨	DH-IPC-HDW2449TP-S-LED-SY IPC IR Dome Camera 	٨١,٥٤٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2688 x 1520) @20 fps, and supports (2560x1440) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in Mic. - 12 VDC/PoE power supply. - IP67 protection.
٢٩	DH-IPC-HDW3449TMP-AS-LED 4MP Full Colour 	٨٧,٥٩٠,٠٠٠		<ul style="list-style-type: none"> - 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 x 1520) @ 30 fps - H.265 codec, high compression rate, low bit rate - Built-in Warm LED, max. LEDs distance: 30 m - Supports max. 256 G Micro SD card, built-in Mic - 12V DC/POE power support - IP67 protection - SMD Plus Lens=2.8 mm

رديف	موديل	قيمة	تصوير كا	مخصفات فني
٣٠	DOME DH-IPC-HDW2449TP-S-IL IPC IR Bullet Camera 	٨٣,٥٨٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light/IR LED, the max. illumination distance is 30 m and - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - SMD Plus.
٣١	DH-IPC-HFW1431SP-SI IPC IR Bullet Camera 	٥١,٦٢٠,٠٠٠		<ul style="list-style-type: none"> - 4MP, 1/3" CMOS image sensor, low illuminance, high image definition - Outputs 4MP (2560 × 1440) @25/30 fps, and supports max. 4MP (2688 × 1520)@20 fps - H.265, high compression rate, ultra-low bit rate - Built-in IR LED, max. IR distance: 30 m - disconnection, IP conflict, illegal access, voltage detection - 12V DC/PoE power supply - IP67, protection Lens=2.8 mm
٣٢	DH-IPC-HFW1431SP-SI IPC IR Bullet Camera 	٥٤,٠٠٠,٠٠٠		<ul style="list-style-type: none"> * 4Megapixel progressive CMOS - * H.265 & H.264 dual-stream encoding - 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) * WDR(120dB)- *Focal Length 2.8 mm *Max IR Length 30m *IP67 / *Casing Metal+Plastic
ميكروفون دار				
٣٣	DH-IPC-HFW1430SP-A Entry IR Fixed-focal Bullet Network Camera 	٥٢,٨٥٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/3" CMOS image sensor, low luminance, and high definition - Outputs max. 4 MP (2560 × 1440)@25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate - Built-in IR LED, and the max. illumination distance is 30 m. - Built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection
استارلايت				
٣٤	DH-IPC-HFW2441SP-S-SI IPC IR Bullet Camera	٦٩,٠٠٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440@25/30 ps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply. - IP67 protection. - SMD Plus.
٣٥	DH-IPC-HFW2441TP-AS IPC IR Bullet Camera	٨٤,٣١٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image.-Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440@25/30 fps. - Support Triple Stream -H.265 codec, high compression rate, ultra-low bit rate. -Built-in IR LED, and the max. illumination distance is 80 m. ; supports max. 256 G Micro SD card; built in MIC. 12 VDC/PoE power supply, easy for installation. IP67 , IK10 (optional) protection. SMD Plus.
دوال لاي				
٣٦	DH-IPC-HFW1439S1-A-IL NEW	٤١,٨٥٠,٠٠٠		
دید در شب رنگي ميكروفون دار				
٣٨	DH-IPC-HFW1439S1-A-LED 4MP Entry Full-color Fixed-focal Bullet Network Camera	٦٠,٦٢٠,٠٠٠		<ul style="list-style-type: none"> - 1/3" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2560 × 1440)@25/30 ps. - H.265 codec, high compression rate, ultra-low bit rate. - ROI, SMART H.264/H.265+, flexible coding, applicable to various - 12 VDC/PoE power supply. - IP67 protection.
٣٩	DH-IPC-HFW2439S-S-IL Smart Fixed-focal Bullet WizSense Network Camera 	٨٣,٥٨٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image. - Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560 × 1440 @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light/IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m. - Supports max. 256 G Micro SD card; built in MIC. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - SMD Plus.
٤٠	DH-IPC-HFW2439SP-SA-LED 	٧٦,٧٧٠,٠٠٠		<ul style="list-style-type: none"> - 4MP, 1/3" CMOS image sensor, low illuminance, high image definition - Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP (2688 × 1520) @ 20 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in warm lights, max. illumination distance: 30 m - Supports max. 256 G Micro SD card and built-in Mic - 12V DC/PoE power supply - IP67 protection
٤١	DH-IPC-HFW2439S-S-LED Full-color Fixed-focal Bullet Wizsense Network Camera	٨٣,٥٨٠,٠٠٠		<ul style="list-style-type: none"> - 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition - Outputs max. 4 MP (2688 × 1520)@20 fps, and supports 2560×1440@25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in Mic. - 12 VDC/PoE power supply. - IP67 protection. - SMD Plus.
٤٢	DH-IPC-HFW2439EP-AS-LED-SI IPC IR Bullet Camera	١١٤,١٦٠,٠٠٠		<ul style="list-style-type: none"> 4MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 4MP (2688 × 1520) @ 30 fps - Built-in Warm LED, max. LED distance: 30 m - Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, card, built in Mic - 12V DC/PoE power support - IP67 protection Lens=3.6 mm

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
MOTORIZED B		موتورایز		
۱۱	DH-IPC-HFW۲۴۹۱TP-ZS Lite IR Vari-focal Bullet Network Camera 	۱۳۵,۳۸۰,۰۰۰		<p>image. - Outputs max. 4MP (2688×1520) @25fps, and supports 2560×1440 (2560×1440) @25/30fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in IR LED, and the max illumination distance is 60m. - Supports SD card recording, supports max. 256GB Micro SD card; built-in MIC. - 12V DC/PoE power supply, easy for installation. - IP67, IK10 (optional) protection. - SMD Plus. Lens=2.7-13.5 mm</p>
۲MP IP Camera				
۱۲	DH-IPC-HDW۱۲۳۰SP IPC IR Dome Camera 	۱۸,۰۰۰,۰۰۰		<p>1/2.7" 2Megapixel progressive CMOS - H.265 & H.264 dual-stream encoding - 25/30fps@1080P(1920x1080) - DWDR, Day/Night(ICR), 3DNR, HLC, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - 2.8 mm fixed lens (3.6mm optional) - Max IR LEDs Length 30m - IP67, PoE</p>
استارلایت				
۱۳	DH-IPC-HDBW۲۲۳۰EP-S-S۲ IR Mini Dome Network Camera 	۱۶,۵۱۰,۰۰۰		<p>2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs 2MP (1920 × 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in IR LED, max IR distance: 30 m - Supports max. 256 GB Micro SD card - 12V DC/PoE power support - DWDR - IP67, IK10 protection grade Metal Lens=3.6 mm</p>
۱۴	DH-IPC-HDBW۲۲۳۱EP-S-S۲ IR Mini Dome Network Camera 	۵۰,۷۷۰,۰۰۰		<p>2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition - Outputs 2MP (1920 × 1080) @25/30 fps - Support triple stream - H.265 codec, high compression rate, ultra-low bit rate - Built-in IR LED, max IR distance: 30 m - Supports max. 256 GB Micro SD card - 12V DC/PoE power supply - IP67, IK10 protection - WDR Metal Lens=3.6 mm</p>
۱۵	DH-IPC-HDW۲۲۴۱TP-S IPC IR Dome Camera 	۵۱,۱۵۰,۰۰۰		<p>2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.-Outputs max. 2 MP (1920 × 1080) @25/30 fps - Support Triple Stream-H.265 codec, high compression rate, ultra-low bit rate - .Support Triple Stream-H.265, flexible coding, applicable to various bandwidth and storage environments-Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes-Intelligent detection- Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)-Supports max. 256 G Micro SD card; built in MIC-32 VDC/PoE power supply-IP67 protection-.SMD Plus.</p>
۱۶	DH-IPC-HDW۲۲۳۰TP-AS-S۲ IPC IR Dome Camera 	۱۶,۵۹۰,۰۰۰		<p>2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs 2MP (1920 × 1080) @25/30 fps - H.265 coding, high compression ration, low bit rate - Built-in IR LED, max IR distance: 30 m - Supports max. 256 GB Micro SD card and built-in Mic - 12V DC/PoE power supply - IP67 protection Metal + Plastic</p>
۱۷	DH-IPC-HDW۲۲۳۱TP-AS-S۲ IPC IR Dome Camera 	۵۰,۰۰۰,۰۰۰		<p>2MP Lite IR Fixed-focal Eyeball Network Camera- 2MP, 1/2.8" CMOS image sensor-Outputs max. 2MP (1920 × 1080) @25/30 fps- H.265 codec- Built-in IR LED, max. IR distance: 30 m-Supports max. 256 GB Micro SD card, built-in Mic-12V DC/PoE power supply- IP67 protection- WDR,/Min. illumination /IP67 0.002 Lux @F1.6-Lens type Fixed-focal-Casing Metal + plastic</p>
دوال لایت				
۱۸	DH-IPC-HDW۱۲۳۹T1P-A-IL 	۵۰,۶۲۰,۰۰۰		<p>2-MP 1/2.8" CMOS image sensor, low luminance, and highdefinition image. - Outputs max. 2 MP (1920 × 1080) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in multi-core light, the max. IR distance is 30 m and the max.warm light distance is 30 m. - Built-in Mic. - 12 VDC/PoE power supply, easy for installation. - IP67 protection. - Supports human detection.</p>
دید در شب رنگی				
۱۹	DH-IPC-HDW۱۲۳۹T1-LED-S۲ IPC IR Dome Camera 	۱۶,۰۰۰,۰۰۰		<p>* 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition * Outputs max. 2MP (1920 × 1080) @25/30 fps- * H.265 codec, high compression rate, ultra-low bit rate-Built-in LEDs, / * IP67 protection * max LED distance: 30 m- ROI, SMART H.264/H.265- / * Casing Metal + plastic * 12V DC/PoE power support- * Focal Length 2.8 mm</p>

رديف		موديل	قيمة	تصوير كا	مشخصات فني
ميكروفون دار					
٥٤	DOME	DH-IPC-HDW1239T1-A-LED-S5 IPC IR Dome Camera 	٦٠,٦٢٠,٠٠٠		<ul style="list-style-type: none"> * 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition - Outputs max. 2MP (1920 × 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate-Built-in LEDs / * IP67 protection * max LED distance: 30 m- ROI, SMART H.264/H.265- / *Casing Metal + plastic * 12V DC/PoE power support- Focal Length 2.8 mm
٥٥		DH-IPC-HFW1239TP-AS-LED-S2 Lite Full-color Fixed-focal Eyeball Network Camera 	٦٥,٦٢٠,٠٠٠		<ul style="list-style-type: none"> 2-MP, 1/2.8" CMOS image sensor, low illuminance, high image definition. - Outputs max. 2MP (1920 × 1080) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm lights, max. illumination distance: 30 m. Supports max. 256 GB Micro SD card and built-in Mic. - 12V DC/PoE power supply. - IP67 protection. Lens=2.8 mm
٥٦	BULLET	DH-IPC-HFW1239S1 IPC IR Bullet Camera 	٣٧,٥٩٠,٠٠٠		<ul style="list-style-type: none"> * 2-MP 1/2.8" CMOS image sensor, low illuminance, high image definition. * H.265, high compression rate, ultra-low bit rate. / *Lens Type :Fixed-focal / Focal Length 3.6 mm Casing :plastic, Front cover: Metal / *12 VDC/PoE *The max. illumination distance is 30 m. / PoE power supply. / IP67 protection.
٥٧		DH-IPC-HFW1239S IPC IR Bullet Camera 	١٥,٠٠٠,٠٠٠		<ul style="list-style-type: none"> * 2MP ENTRY IR Fixed-Focal Bullet Netwok Camera * 2MP, 1/2.8" CMOS image sensor /Focal Length 3.6mm & 2.8 / *Metal + plastic * Outputs max. 2MP (1920 × 1080) @25/30 fps * H.265 codec* Built-in efficient IR illuminator, and the max. illumination distance is 30 m - ROI, SMART H.264+/H.265+, flexible coding, * 12V DC/PoE power supply / * IP67 protection /
٥٨		DH-IPC-HFW1239SP-S IPC IR Bullet Camera 	١٧,٥٩٠,٠٠٠		<ul style="list-style-type: none"> * 2MP, 1/2.7" CMOS image sensor * Outputs 2MP (1920 × 1080)@25/30 fps * H.265 codec,high compression rate, ultra-low bit rate Focal Length: 2.8mm & 3.6 mm * Built-in IR LED, max IR distance: 30 m * Supports max. 256 GB Micro SD card * 12V DC/POE power supply *IP67 protection *Intelligent detection *Casing : Metal
دواں لایت					
٥٩	BULLET	DH-IPC-HFW1239S1P-A-IL 	٦٠,٦٢٠,٠٠٠		<ul style="list-style-type: none"> 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. - Outputs max. 2 MP (1920 × 1080)@25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m. - Abnormality detection: Motion detection, video tampering, audio detection, network disconnection, IP conflict, illegal access. - Built in Mic. - 12 VDC/PoE power supply, easy for installation. - IP67 protection.
٦٠		DH-IPC-HFW1239S1-A-LED-S5 IPC Bullet Camera 	١٩,٥٨٠,٠٠٠		<ul style="list-style-type: none"> * 2MP, 1/2.7" CMOS image sensor * 2MP (1920 × 1080) @25/30 fps- * H.265 codec- Built-in LEDs, max LED distance: 15 m- * 12V DC/PoE power support * IP67 protection-Lens Focal Length 2.8 mm *Casing : Metal + plastic
٦١		DH-IPC-HFW1239SP-SA-LED-S2 IPC IR Bullet Camera 	٦٥,٦٢٠,٠٠٠		<ul style="list-style-type: none"> 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition - Outputs max. 2MP (1920 × 1080) @25/30 fps - H.265 codec, high compression rate, ultra-low bit rate - Built-in warm lights, max. illumination distance: 30 m - ROI, SMART H.264+/H.265+, flexible coding, applicable to various Supports max. 256 GB Micro SD card and built-in Mic - 12V DC/PoE power supply - IP67 protection Lens=3.6 mm
٦٢	BULLET	DH-IPC-HFW1239SP-S-LED-S2 IPC IR Bullet Camera 	٦٧,٥٨٠,٠٠٠		<ul style="list-style-type: none"> - 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. - Outputs max. 2 MP (1920 × 1080) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in Mic. - 12 VDC/PoE power supply. - IP67 protection. - SMD Plus.
٦٣		DH-IPC-HFW1239SP-S-LED-S2 IPC IR Bullet Camera 	٦٨,٥٨٠,٠٠٠		<ul style="list-style-type: none"> - 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image. - Outputs max. 2 MP (1920 × 1080) @25/30 fps. - H.265 codec, high compression rate, ultra-low bit rate. - Built-in warm light and the max. illumination distance is 30 m. - Supports max. 256 G Micro SD card; built in Mic. - 12 VDC/PoE power supply. - IP67 protection. - SMD Plus.

رده	مدل	قیمت	تصویر کالا	مشخصات فنی
SPEED DOME				
۵۲	SDI۹۱۴۲۵GB-HNR ۳۰x Starlight IR Network PTZ Camera 	۱۵۲,۱۰,۰۰۰		<p>1/2.8" STARVIS™ CMOS.</p> <ul style="list-style-type: none"> - 25x optical zoom. - Starlight technology. - Max. 25/30fps@4M. - IR distance up to 100 m. - Perimeter protection. - Face detection. - SMD 4.0. - IP66.
	DH-SD5A1۴۳۲GB-HNR ۳۰x Starlight IR WizSense Network PTZ Camera 	۷۰,۰۰۰		<p>1/2.8" 4Megapixel STARVIS™ CMOS.</p> <ul style="list-style-type: none"> - Powerful 32x optical zoom. - Max. 25.30 fps@4M. - IR distance up to 150 m. - Auto Tracking 3.0. - Face Detection. - SMD 4.0. - PoE+. - IP67, IK10.
	DH-SD5A1۴۴۰GB-HNR ۳۰x Starlight IR WizSense Network PTZ Camera 	۹۳۸,۰۰۰		<p>1/2.8" 4Megapixel STARVIS™ CMOS.</p> <ul style="list-style-type: none"> - 45x optical zoom. - Starlight technology. - Max. 25/30fps@4M. - IR distance up to 150 m. - Auto-tracking 3.0. - Perimeter protection. - Face detection. - SMD 4.0. - IP67, IK10.
NVR ۱Channel				
۵۴	DHI-NVR11۰۱HS-S1/H Up to ۱MP Resolution preview&playback	۱۶,۹۰,۰۰۰		<p>* 4-ch@1080P(30FPS) *Smart H.265+/Smart H.264+/H.265/H.264 *VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P-HDD Resolution 8MP/5MP/3MP/1080P/720P/D1/CIF Decoding Capability *80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding. *USB 1 front USB 2.0 port, 1 rear USB 2.0 port *1 SATA 2.0 port, up to 8 TB for a single HDD.</p>
	DHI-NVR11۰۱HS-1KS1 Up to ۱MP Resolution preview&playback	۵۶,۹۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. • Max. decoding capability: 6 × 1080p@30fps. • Max. 80/80/60 Mbps incoming/recording/outgoing bandwidth. • Supports IP cameras with a resolution up to 12 MP. • AI by Recorder supports 4-channel SMD. • AI by Camera supports perimeter protection and SMD. • Supports one-click arming and disarming.</p>
	DHI-NVR11۰۱HS-1KS1/L Up to ۱MP Resolution preview&playback	۱۰,۰۰۰,۰۰۰		<p>New 4.0 user interface, Security baseline 2.1. - H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch - Max. decoding capability: 8 × 1080p@30fps. Supports adaptive decoding - Supports mainstream cameras of ONVIF and RTSP protocols - P2P remote surveillance, video play on mobile device - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K - AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD - Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches.</p>
۵۵	DHI-NVR11۰۱-1KS1/L Up to ۱MP Resolution preview&playback	۷۰,۰۰۰,۰۰۰		<p>New 4.0 user interface, Security baseline 2.1. - H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch - Max. decoding capability: 8 × 1080p@30fps. Supports adaptive decoding - Supports mainstream cameras of ONVIF and RTSP protocols - P2P remote surveillance, video play on mobile device - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K - AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD</p>
	DHI-NVR11۰۱HS-1Y Up to ۱MP Resolution preview&playback	۷۰,۰۰۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format - Max. decoding capability: 6 × 1080p@30fps. Supports adaptive decoding - 1-channel face detection and recognition (AI by NVR); 1-channel perimeter protection (AI by NVR); up to 10 face databases and 5,000 face images; 4-channel SMD Plus (AI by NVR); - 2.1 k cameras</p>

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
NVR ۸Channel				
۱۱	DHI-NVR11۰AHS-S³ 8 CH Up to ۱۲MP Resolution preview&playback	۵۱,۶۲۰,۰۰۰		<p>New 4.0 user interface</p> <ul style="list-style-type: none"> - P2P remote surveillance, video play on mobile device - 4-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.264 - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P
۱۲	DHI-NVR21۰AHS-S³ 8 CH Up to ۱۲MP Resolution preview&playback	۸۲,۲۳۰,۰۰۰		<p>New 4.0 user interface</p> <ul style="list-style-type: none"> - P2P remote surveillance, video play on mobile device - 4-ch@1080P(30FPS), self-adaptive decoding capability - Support for mainstream cameras of ONVIF and RTSP protocol - Smart H.265+/Smart H.264+/H.265/H.264 - VGA/HDMI simultaneous video output, maximum resolution of HDMI is 1080P
۱۳	DHI-NVR21۰AHS-FKS³ 8 CH Up to ۱۲MP Resolution preview&playback	۸۸,۴۵۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEGdecoding formats.</p> <ul style="list-style-type: none"> Max. decoding capability: 6 × 1080p@30 fps. Max. 80/80 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports perimeter protection and SMD Plus. Supports one-click arming and disarming.
۱۴	DHI-NVR11۰AHS-FKS³ 8 CH Up to ۱۲MP Resolution preview&playback	۱۰۱,۶۵۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEGdecoding formats.</p> <ul style="list-style-type: none"> Max. decoding capability: 8 × 1080p@30 fps. Max. 80/80 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports face detection and recognition, perimeterprotection, SMD Plus, people counting, stereo analysis and heatmap. Supports EPTZ, and one-click arming and disarming.
۱۵	DHI-NVR11۰AHS-EI 8 CH Up to ۱۲MP Resolution preview&playback	۱۰۵,۱۰۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.</p> <ul style="list-style-type: none"> - Access, storage or forwarding at 80 Mbps. - Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding. - AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus. - AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map. - Connected to the third-party network cameras. - Security baseline 2.3.
NVR ۱۶Channel				
۱۶	DHI-NVR11۱۶-FKS³ 16 CH Up to ۱۲MP Resolution for Preview and Playback	۱۳۶,۹۲۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEGdecoding formats.</p> <ul style="list-style-type: none"> Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps. Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth. Supports IP cameras with a resolution up to 12 MP. AI by Recorder supports 4-channel SMD Plus. AI by Camera supports face detection and recognition, perimeterprotection, SMD Plus, people counting, stereo analysis and heatmap. Supports EPTZ, and one-click arming and disarming.
۱۷	DHI-NVR11۱۶HS-EI 16 CH Up to ۱۲MP Resolution for Preview and Playba	۱۶۲,۷۰۰,۰۰۰		<p>Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding.</p> <ul style="list-style-type: none"> AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus. AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map. BANDWITH: 256 Mbps incoming 1 SATA port, up to 16 TB.The maximum HDD capacity

ردیف		مدل	قیمت	تصویر کالا	مشخصات فنی
۷۹		DHI-NVR۴۲۱۶-EI 16 CH Up to ۱۶ MP Resolution preview&playback	۱۹۳,۳۸۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Access, storage or forwarding at 256 Mbps (180 Mbps when AI function enabled). - Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding. - Connected to the third-party network cameras. - Security baseline 2.3.</p>
		DHI-NVR۵۲۱۶-EI 16 CH Up to ۲۴ MP Resolution preview&playback	۲۷۵,۳۸۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Max. decoding capability: 32 × 1080p@30 fps or 16 × 4MP@30fps. - Max. 384 Mbps incoming/recording/outgoing bandwidth. - Support AcuPick with Max. 16-Channel. - Support N+M cluster. - MD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.</p>
		NVR۴۲۱۶-۴KS2 16 Channel ۱U ۱6PoE WizSense Network Video Recorder 16 CH	۱۶۱,۵۰۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. - Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30fps. - Max. 160/160/80 Mbps incoming/recording/outgoing bandwidth. - Supports IP cameras with a resolution up to 12 MP. - AI by Recorder supports 4-channel SMD Plus. - AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map. - Supports EPTZ, and one-click arming and disarming.</p>
NVR ۳۲Channel					
۸۲		DHI-NVR۱۴۲۲۲-۴KS2 32 CH ۴HDD maximum resolution of HDMI is ۴K	۲۶۲,۰۰۰,۰۰۰		<ul style="list-style-type: none"> - 16/32-channel IP video access - Smart H.265+/Smart H.264+/H.265/H.264; H.265 auto switch - Max 200 Mbps incoming bandwidth - Up to 8MP resolution for preview and playback - 8-channel decoding@1080p (30 fps) - AI by Camera: Perimeter protection; SMD Plus; people counting; heat map
		DHI-NVR۱۴۲۲۲-EI 32 CH ۴HDD maximum resolution of HDMI is ۱۶MP	۲۲۷,۶۹۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding. - AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus. * Max 200 Mbps incoming bandwidth 2 SATA ports, up to 16 TB.The maximum HDD capacity</p>
		DHI-NVR۱۴۲۲۲-۴KS2 32 CH ۴HDD maximum resolution of HDMI is ۱۶MP	۱۹۳,۸۰۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats. - Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30fps. - Max. 160/128/60 Mbps incoming/recording/outgoing bandwidth. - Supports IP cameras with a resolution up to 12 MP. - AI by Recorder supports 2-channel SMD Plus. - AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heatmap. - Supports EPTZ, and one-click arming and disarming.</p>
۸۳		DHI-NVR۰۲۲۲-EI 32 CH ۴HDD maximum resolution of HDMI is ۲۴MP	۱۸۱,۵۰۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30fps. - Max. 384 Mbps incoming/recording/outgoing bandwidth. - Support AcuPick with Max. 16-Channel. Support N+M cluster. - AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. - AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.</p>
		DHI-NVR۰۲۲۲-EI 32 CH ۴HDD maximum resolution of HDMI is ۲۴MP	۵۱۵,۹۲۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30fps. - Max. 384 Mbps incoming/recording/outgoing bandwidth. - Support AcuPick with Max. 16-Channel. - Support N+M cluster. - Support Raldo/1/5/6/10. - AI by recorder: 2-channel face detection and recognition, 4-channel SMD Plus</p>
		DHI-NVR۰۲۲۲-EI 32 CH ۴HDD Up to ۱۶MP Resolution preview&playback	-		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format. - Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30fps. - Max. 384 Mbps incoming/recording/outgoing bandwidth. - Support AcuPick with Max. 16-Channel. - Support N+M cluster. - Support Raldo/1/5/6/10. - AI by recorder: 2-channel face detection and recognition, 4-channel SMD Plus</p>

ردیف	مدل	قیمت	تصویر کالا	مشخصات فنی
NVR ۶۴Channel				
۸۸	DHI-NVR51664-EI ۶۴ CH ۱HDD <i>Wiz Sense</i> Up to ۳۲ MP Resolution preview&playback	۶۸۰,۰۰۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.</p> <ul style="list-style-type: none"> Max. decoding capability: 32 × 1080p@30 fps or 32 × 2MP@30 fps. Max. 384 Mbps incoming/recording/outgoing bandwidth. Support AcuPick with Max. 16-Channel. Support N+M cluster. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus.
	DHI-NVR51864-EI ۶۴ CH ۱HDD <i>Wiz Sense</i> Up to ۳۲ MP Resolution preview&playback	۹۰۰,۵۹۰,۰۰۰		<p>Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format.</p> <ul style="list-style-type: none"> 32-channel 1080p self-adaptive decoding capability. Support Raid0/1/5/6/10. Max. 384 Mbps incoming/recording/outgoing bandwidth. AI by recorder: 2-channel face detection and recognition, 4-channel perimeter protection, and 8-channel SMD Plus. AI by camera: Face detection and recognition, perimeter protection, SMD Plus, metadata, ANPR, stereo analysis, heat map, and people counting.
	DHI-NVR51A-64C-XI ۶۴ CH ۱HDD <i>Wiz Mind</i> Up to ۳۲ MP Resolution preview&playback	۱,۶۰۰,۰۰۰,۰۰۰		<p>Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.</p> <ul style="list-style-type: none"> Max. decoding capability: 32 × 1080p@30 fps. Max. 1280/1280/1024 Mbps incoming/recording/outgoing bandwidth. Supports AcuPick with up to 64 channels. Supports EPTZ, One-click Arming & Disarming. Security baseline 2.3. Bandwidth: 1280 Mbps incoming